

Rotary Laser



Complete set includes



Data Specifications

- Fully automatic leveling
- Electronic vials and positioning motors
- Controlled by temperature-stables sensors for auto alignment
- Reliable and easy to operate

PERFORMANCE

H: ±15" V: ±20" Auto Level Accuracy ≤ ± 1mm/1.5m **Down Point Accuracy** ≤1mW, Class II **Output Power** 520nm Green Beam **Laser Wave Auto Level Range** ±5°

Working Range with Receiver (dia) 1000m **Remote Control Distance** 25m ±5°

Slope Range **Scanning Speed** 0/60/120/300/600 r.p.m. (Adjustable) **Scanning Width**

0.10°, 40°, 90°, 180° (Adjustable) DC4.8-6V (N-H Rechargeable Battery x4) Power Time in Continuous Use 15 hours (N-H Rechargeable Battery x4) -20°C - 50°C **Working Temperature**

Dust Proof and Slash Proof IP54 Dimension 160 (L) x 160(W) x 185(H) mm **Net Weight** 3.0kg including batteries **Gross Weight**

Remote Controller, detector with Clamp, Rechargeable Battery x4, Accessories Charger, Plastic Carrying Case

Headquarters:

Datavägen 21B SE-436 32 Askim, Sweden info@satlabgps.com

Regional Offices:

Jičín, Czech Republic Ankara, Turkey Scottsdale, USA Singapore, Singapore Warsaw, Poland

www.satlabgps.com